



5 - 50 kVA

## AVR11 SERIES

FULL AUTOMATIC VOLTAGE REGULATOR

### GENERAL SPECIFICATIONS

- Non-linear charges drive
- 1 phase input 1 phase output
- Wide power and voltage interval
- High reliability thanks to Microprocessor and Smart Driver
- Fast Regulation
- High efficiency
- Load transfer to Bypass via pole charge switch
- Safe and economic usage
- Low and overvoltage protections
- Overload protection(optional)
- Digitally displayed status, input & output measurements





5 - 50 kVA

## TECHNICAL SPECIFICATIONS

MODEL	AVR 1105	AVR 1107	AVR 1110	AVR 1115	AVR 1120	AVR 1125	AVR 1130	AVR 1140	AVR 1150
Power kVA	5	7,5	10	15	20	25	30	40	50
<b>REGULATOR INPUT</b>									
In.Vol.Correct.Interval	165 - 255 / 110 - 240 VAC (Optional)								
In.Vol.Operating.Interval	90 - 285 VAC								
Operation Frequency	47...65 Hz								
Line Input Protection	Overcurrent, Low and High voltage protection								
Current at input	24	36	48	72	96	120	144	192	240
<b>REGULATOR OUTPUT</b>									
Output Voltage	220 / 230 / 240 VAC RMS $\pm$ 1 %								
Overloading	10 Sec. 200 % Load								
Correction Speed	~ 90 Volt / Sec.								
Upturn Period	~ 90 Volt / Sec. ( 160 VAC - 260 VAC)								
Output Protection	Protects load by opening the circuit when overburden, short circuit occurs								
Current at output	18	27	36	54	72	90	108	144	180
<b>GENERAL</b>									
Working Principle	Servo Motor, Microprocessor Controlled, Full Automatic								
Cooling	Smart Fan System								
Measured Value Monitor.	TRUE RMS Panel Voltmeter (74x74mm) output voltage and line voltage monitorization								
Total Efficiency	> 96 %								
Mechanical By-pass	"Manually Controlled Line - PAKO Switch Selects Voltage Regulator" Switch Turn On / Off								
Protection Level	IP 20 // IP 54 (Optional)								
<b>ENVIRONMENTAL</b>									
Working Temperature	-10 °C / 50 °C								
Storage Temperature	-25 °C / + 60 °C								
Relative Humidity	< 90 %, DIN ( 40040 )								
Working Altitude	< 2000 m.								
Acoustic Level	< 50 dB								
Standards	CE / ISO 9001								
<b>DIMENSIONS</b>									
HxWxD (cm)	30x45x37			34x59x42		85x50x52		85x50x62	
Weight (kg)	30	34	47	55	95	110	130	155	180



**EPI UPS (Asia-Pacific) Pte Ltd**  
101 Thomson Road, United Square,  
#06-01/06, Singapore 307591

**EPI UPS (Italy) SRL**  
Via Decio Raggi, 411  
Forli 447121, Italy

Website: [www.epi-ups.com](http://www.epi-ups.com) Tel. +65-6809 3073 Fax: +65-6491 5230

